



DEAN BENNETT SUPPLY CO

Toll Free : 800 - 621 - 4291

# 35 GPM 4" Stainless Steel Submersible Pumps

## 35 GPM Series 4" Submersible Pumps 1 hp thru 7-1/2 hp

ALL PRICES FOR 3 WIRE W/CONTROL BOX COMPLETE PUMPS  
DEPTH TO WATER LEVEL IN FEET - CAPACITIES IN GALLONS PER MINUTE

HP & Model	Stages	Disch PSI	20	40	60	80	100	120	140	160	180	200	220	240	260	300	350	400	450	500	550	600	650	700	
1 HP 4F35S10	4	0 PSI	20	40	60	80	100	120	140	160	180	200	220	240	260	300	350	400	450	500	550	600	650	700	
		20	42	37	32	25																			
		40	30	22																					
		60																							
1-1/2 HP 4F35S15	5	0 PSI			47	43	40	36	31	25	10														
		20	46	43	39	35	30	23																	
		40	38	33	28																				
		60	26	15																					
2 HP 4F35S20	7	0 PSI			50	48	45	43	40	37	34	30	26	19											
		20		47	45	42	39	36	33	29	24														
		40		41	38	35	32	28	22																
		60		34	31	26	19																		
3 HP 4F35S30	10	0 PSI				49	47	45	44	42	40	38	36	33	28	17									
		20			48	47	45	43	41	39	37	35	33	30	27	18									
		40			45	43	41	39	37	35	32	29	26	22	17										
		60			40	38	36	34	31	28	25	20													
5 HP 4F35S50	16	0 PSI					50	49	48	47	46	45	44	42	39	35	31	26	20						
		20					49	48	47	46	45	44	43	41	39	36	32	27	21						
		40				49	48	47	46	45	44	42	41	40	39	36	32	27	21						
		60				47	46	44	43	42	41	40	38	37	35	32	28	22							
7-1/2 HP 4F35S75	23	0 PSI							50	49	48	47	46	45	43	40	38	36	33	31	28				
		20							49	48	47	46	45	43	41	39	36	34	31	28	24				
		40							49	48	47	46	45	43	41	39	36	34	31	28	24	19			
		60						49	48	47	46	45	44	43	42	41	39	36	34	31	28	25	20		

NOTE: Pipe friction loss in drop pipe is not included in chart above. 3 HP and larger pumps may require a flow inducer to give proper flow in larger wells. All 35 GPM and larger pumps require a 2" check valve be installed just above the pump, since there is not a built in check valve.

# 55 GPM 4" Stainless Steel Submersible Pumps

## 55 GPM Series 4" Submersible Pumps 1-1/2 hp thru 7-1/2 hp

ALL PRICES FOR 3 WIRE W/CONTROL BOX COMPLETE PUMPS  
DEPTH TO WATER LEVEL IN FEET - CAPACITIES IN GALLONS PER MINUTE

HP & Model	Stages	Disch PSI	20	40	60	80	100	120	140	160	180	200	220	240	260	300	350	400	450	500	550	
1-1/2 HP 4F55S15	4	0 PSI	20	40	60	80	100	120	140	160	180	200	220	240	260	300	350	400	450 <td>500</td> <td>550</td>	500	550	
		20	70	60	47	33																
		40	42	23																		
		60																				
2 HP 4F55S20	5	0 PSI			75	69	61	51	42	29												
		20	74	68	59	50	38	15														
		40	58	45	34																	
		60	30																			
3 HP 4F55S30	7	0 PSI			75	71	66	61	55	47	39	31										
		20		75	70	65	59	53	46	38	28											
		40		63	57	50	43	34	15													
		60		48	40	32																
5 HP 4F55S50	11	0 PSI						74	71	68	64	61	57	53	44	30						
		20					73	70	67	64	60	56	52	47	42	31						
		40			72	69	66	63	59	55	50	45	40	35	30							
		60			65	62	58	53	49	44	39	33	25									
7-1/2 HP 4F55S75	18	0 PSI							75	74	72	71	73	71	66	62	56	49	41	33		
		20							75	74	72	70	68	64	62	57	50	42	34	20		
		40						72	71	70	68	66	63	61	59	57	51	43	35	24		
		60					72	71	70	68	66	63	61	59	57	51	43	35	25			

NOTE: Pipe friction loss in drop pipe is not included in chart above. 3 HP and larger pumps may require a flow inducer to give proper flow in larger wells. All 55 GPM and larger pumps require a 2" check valve be installed just above the pump, since there is not a built in check valve.